



TECHNICAL DATA SHEET

Juillet , 2003

ROOFCRAFT-95- BASE-F/R-FIBREGLASS

ROOFCRAFT-95-BASE-F/R-FIBREGLASS IS MADE FROM A 1/2" HIGH-DENSITY FIRE-RESISTANT FIBERBOARD. A FILM-SURFACED SBS MODIFIED MEMBRANE IS LAMINATED TO THE TOP OF THE FIBERBOARD. THE SELVAGE EDGE BECOMES SELF-ADHERING ONCE THE RELEASE FILM IS REMOVED. **ROOFCRAFT-95-BASE-F/R-FIBREGLASS** MAY BE APPLIED BY MECHANICAL ATTACHMENT, HOT ASPHALT OR COLD PROCESS ADHESIVE. THE FIBERBOARD CONTENT OF THIS PRODUCT CONFORMS TO CAN/ULC-S-706, ASTM C-208 AND CAN/ULC-S-102 STANDARDS.

CHARACTERISTICS	UNIT	TYPICAL VALUE
WIDTH:	mm (in)	900 (36)
LENGTH:	mm (in)	2600 (102)
THICKNESS:	mm .	14.0
REINFORCEMENT : FIBREGLASS MAT	g	95
TOP SURFACE:	FILM	THERMOFUSIBLE PLASTIC
WEIGHT:	kgs (lbs)	13.7 (30.2)
QUANTITY PER PALLET :	PANELS	75
FLAME SPREAD RATING*	-----	<25
SMOKE DEVELOPMENT*	-----	<25
DENSITY*	Kg/m ³ (lbs/ft ³)	232 (14.5)
R-VALUE PER 25 MM THICKNESS*	-----	3.1
WATER ABSORPTION*	%	3.5
RESISTANCE TO COMPRESSION* (10% DEFORMATION)	KPa (psi)	138 (25)

*Tests conducted without the membrane layer