

TECHNICAL DETAILS	
WEIGHT/ROLL	WEIGHT/SQUARE
80 lbs. 36.3 kg	40 lbs. 18.1 kg
WIDTH	LENGTH
39 $\frac{3}{8}$ " 1 m	66' 20.1 m
THICKNESS	COVERAGE
55 mils nominal	2 square
PERM RATING	ROLLS/PALLET
< 0.1 U.S. perms	30
LAY LINES	
2", 4", 12 $\frac{1}{2}$ ", 18 $\frac{3}{4}$ " 51 mm, 102 mm, 318 mm, 476 mm	

TEST COMPLIANCE	
ASTM D4601 Type II	ASTM D4869
ASTM D226 Type II	ASTM D6757 Type II
ICC APPROVAL ESR-1561	FBC APPROVALS #14807 #15214
ASTM E108 Class A Fire Rating	

FEATURES & BENEFITS
<ul style="list-style-type: none"> <li>Flexor™ SBS polymer modified asphalt</li> <li>Water-resistant underlayment</li> <li>Effective dry-in sheet</li> <li>UL Class A Fire Rated when installed with a Fire Rated Roof Covering</li> </ul>

## FLEXOR™ SBS POLYMER MODIFIED FIBERGLASS UNDERLAYMENT



### PRODUCT USE

Right Start™ UDL is a Flexor™ SBS polymer modified asphalt membrane suitable for use as a water-resistant underlayment or dry-in sheet for steep slope roofing applications to include asphalt shingles, roof tile, and wood shingles and shingles. Right Start™ UDL is approved for use under fire-rated, code-compliant roof coverings. Please consult Malarkey's Technical Services Department for approval of roof systems.

### COMPOSITION & MATERIALS

Right Start™ UDL is manufactured on a durable fiberglass mat, impregnated and coated on both sides with Flexor™ SBS polymer modified asphalt, and surfaced with a mineral release material.

### APPLICATION

Right Start™ UDL shall be applied as specified. It is not intended as a permanently-exposed roofing surface but can be left uncovered for up to 90 days if necessary before the primary roof covering is installed. See Malarkey Specification Manual for specific installation instructions, and/or contact our Technical Services Department for details.

### PRECAUTION

Right Start™ UDL should be stored on end prior to installation to prevent rolls from flattening. Malarkey recommends allowing Right Start™ UDL to warm up and relax prior to application in colder weather. Roof decks should be sound, dry, smooth, meet necessary local requirements, and provide positive drainage. Certain tiles with minimal contact to the surface of Right Start™ UDL may be prone to sliding.

### WARRANTY

Right Start™ UDL is eligible for expanded warranty coverages relative to its use as a single roofing accessory or in combination with others in a complete Malarkey roofing system. Installed separately, it carries a 10-year product warranty against manufacturing defects. Contact your roofing contractor, local distribution center, or Malarkey for full details. See below for TECHNICAL ASSISTANCE contact information.

Right Start™ UDL and other Malarkey products are available throughout North America and Pacific Rim countries.

Visit [WWW.MALARKEYROOFING.COM](http://WWW.MALARKEYROOFING.COM) for additional product information and availability.

Note: Malarkey Roofing Products® inventory SKU designation for this product: UDL

PHYSICAL PROPERTIES	ASTM D4601 TYPE II	TYPICAL RESULTS
Maximum load, CM	44 lbf/in, minimum	Pass
Maximum load, MD	44 lbf/in, minimum	Pass
Pliability	No failures	Pass

### TECHNICAL ASSISTANCE:

Malarkey has technical services assistance available. Contact Malarkey for details:

Call weekdays 7:00 am to 5:00 pm PST,  
at 800.545.1191 or 503.283.1191.  
[technicalinquiries@malarkeyroofing.com](mailto:technicalinquiries@malarkeyroofing.com)

### CORPORATE OFFICE:

3131 N. Columbia Blvd.  
Portland, OR 97217-7472

P.O. Box 17217  
Portland, OR 97217-0217

Telephone: 503.283.1191  
or 800.545.1191

Fax: 503.289.7644