



# GAFLAS®

## STRATAVENT® PERFORATED VENTING BASE SHEET

Formerly GAFLAS® Stratavent® Eliminator™  
Perforated Venting Base Sheet

### Description

GAFLAS® Stratavent® Perforated Venting Base Sheet is a premium-grade roofing felt constructed around a strong glass fiber mat and high-quality asphalt. The bottom of the sheet is granule-surfaced to provide positive venting of any trapped gases under the roof membrane.

- GAFLAS® Stratavent® Perforated Venting Base Sheet is available for nailable and non-nailable substrates.
- GAFLAS® Stratavent® Perforated Venting Base Sheet is unique in the industry: its patent-pending perforated design allows mopping asphalt as the next ply of the roof system is installed. The flow-through asphalt uniformly bonds the GAFLAS® Stratavent® Perforated Venting Base Sheet and the subsequent roof system to the substrate.

### Uses

GAFLAS® Stratavent® Perforated Venting Base Sheet is a venting base sheet designed to be used in various GAFLAS® built-up and RUBEROID® modified bitumen roofing systems. It can be used over both nailable and non-nailable substrates, including certain existing old roof surfaces and isocyanurate foams.

### Advantages

- Provides for venting of pressurized gases beneath the roofing membrane.
- Fire resistant—for use in UL, ULC Class A rated assemblies.
- In re-cover applications, provides an effective means for separating the new roofing membrane from the existing roof system.
- GAFLAS® Stratavent® Perforated Venting Base Sheet provides consistent, uniform spot-attachment of the roofing membrane.
- Wind uplift-resistant; FM Approved up to Class 1-345 (see FM Approval Guide for details).
- Meets requirements for application in all climate zones.
- System guarantees are available for up to 20 years.\*

### Applicable Standards

|                                            |
|--------------------------------------------|
| Meets ASTM D4897, Type II                  |
| FM Approved                                |
| ICC ESR-1274                               |
| Miami-Dade County Product Control Approved |
| State of Florida Approved                  |
| Texas Department of Insurance              |
| UL/ULC Listed                              |

### Product Specifications (nominal)

|                     |                                                 |
|---------------------|-------------------------------------------------|
| Roll Size           | 1.26 squares<br>(133.4 gross sq. ft.) (12.4 m²) |
| Roll Length         | 40.6' (12.4 m)                                  |
| Roll Width          | 39.375" (1.0 m)                                 |
| Approx. Roll Weight | 76 lb (34.5 kg)                                 |



\* See applicable guarantee for complete coverage and restrictions.